

橡膠、塑膠開煉機 Rubber/Plastic Opening Mixing Mill



特性及結構:

1. 底座：為一體式結構，採用鋼板焊接或鑄造制成，作業穩定性高。
2. 襯套：軸承式襯套，外殼採用鑄鋼材質，內襯為高強度軸承。
3. 襯套潤滑：採用強制循環潤滑系統。



周邊鑽孔襯 (選配)  
Drilled roller (optional)  
冷卻效果最好  
This is better cooling



電動調整 (選配)  
Motor power-zoom (optional)  
方便調整兩輪間距  
It's more easy to modify the gap of two rollers.



快拆式擋板 (選配)  
Speedy guide baffle (optional)  
方便拆卸清洗擋板  
It's more easy to clean, and disassemble the guide baffle

CONSTRUCTION AND FEATURES

1. RED: One piece construction of welded steel plate or cast iron provides maximum stability.
2. BUSHING: The bearing type bushing is constructed of cast iron housing and high strength bearing at inside diameter.
3. BUSHING LUBRICATION :Employs automatic circulated lubrication system.

橡膠、塑膠開煉機 Rubber/Plastic Opening Mixing Mill



軸承式襯套  
Bearing Bushing  
採用特殊軸承，確保高精度，運轉順暢。



The bushing is fitted with a special bearing for great precision accuracy, smooth running performance and maximum durability.



雙出軸齒輪箱與萬向接頭的傳動方式 (選配項目)  
特點：運轉穩定，兩輪的間距可放最大程度的調整。  
With the use of double extension shafts and universal coupling for transmission (option)

The operation performance becomes more stable and the space between the two rollers can be regulated to the most extent gap.

規格尺寸(φ xL) Size of rolls	12"x30"	14"x36"	16"x42"	18"x48"	22"x60"	24"x72"	26"x84"
主動電機功率 Main motor power	22kw	30kw	45kw	75kw	110kw	160 kw	220kw
機械重量 Equipment weight	5000kg	6000kg	8000kg	12500 kg	18500kg	26500kg	32000kg
機械尺寸 Install dimension	3400x1300x1500	4120x1430x1960	4500x1550x1900	5100x1750x2150	5300x2000x1800	6200x2450x2200	6600x2550x2300