

## 冷水式出片機 PE&EVA Water Cooling Machine

用途:

本機適用PE&EVA板, 冷卻裁斷, 使之尺寸符合油壓機模具之尺寸。

Applications: This unit is suitable for the cooling and cutting of PE and EVA sheet panels, of which the sizes can be made to fit the mold size of hydraulic machines.

特點:

五輪式皮帶帶動, 無毛刷輪。

可依據客戶需要區分四輪或五輪, 加壓與不加壓式。

Features: Five-wheel belt driven unit, without brush roller.



規格 Dimensions	需要馬力 Horse Power	電熱 Electric Heating	重量 Weight
L600xW180xH160(cm)	5KW	1.5KW	2800kg

## 斜割機 Bevel Skiving Machine (XG-60L)

用途:

運動鞋底、海灘鞋、溜冰鞋、拖鞋、草蓆鞋等鞋底分割。

Use for:

Applications: Sole cutting for sports shoes, beach shoes, rollerskates, sandals, mat-sandals, etc.



規格 Dimensions	馬力 Horse Power	重量 Weight	滾輪轉速 Roller Shaft Speed	加工寬度 Processing Width	上下滾輪中心距 Distance Between Rollers
2,500x1,100x1,500(mm)	5HP	1200kg	120rpm	600mm	140mm

## PE&EVA 電熱式接片機 Electrothermic Type PE&EVA Plate Bonding Machines

本機械設備適用PE&EVA高低發泡有限長度板材, 以電熱熔接方式(不用膠水等任何熔劑), 接著成無限長度, 以方便後續加工。本機械設備使用在玩具沙灘鞋等需要短片多色多樣顏色變化的片色。

This machine is used for the electrothermic melting and bonding(using no adhesives or any hotmelt)of highly and lowly foamed PE and EVA plates,making processings that follow easier.This model is most suitable for the processing of toys,beach sandals,and many others that are bonded with short plates for diverse and multi-color combinations.

規格 Model	加工寬度 Working Width	加工長度 Working Length	加工厚度 Working Thickness	加工硬度 Working Hardness	加工速度 Working Speed	接合率 Bonding Rate
JP-180	600-1800(mm)	10mm at minimum	30-100(mm)	15° - 65°	1piece/min.	over 95%



### 全套配置 Full Configuration

品名 Unit	規格 Model	體積 Dimensions	重量 Weight	馬力 Horse Power	數量 Quantity	備註 Remark
熔切台 Melt-Cutting Machine	1800mm	2260X2420X1500(mm)	800kg	1/2HP	1台one unit	改良機型 New Design
熔接台 Melt-Cutting Machine	1800mm	3450X2420X1500(mm)	1800kg	5.5HP	1台one unit	改良機型 New Design
卷收台 Collecting Machine	1800mm	2330X900X2100(mm)	300kg	2HP	1台one units	卷原板才成卷 Plate material rolling
卷料台車 Maching for Rolling	large	1800X1800X1500(mm)	150kg		2台two units	依工作量再加數量 Units can be increased according to working volume
卷管 Bending Tube	Φ600 mm Φ450 mm	2000X600 (mm) 2000X450 (mm)	120kg 70kg		2支two units 1支one units	依工作量再加數量 Units can be increased according to working volume